

# AARD SHUTTLE 38



## **FEATURES**

#### SAFE WORKING ENVIRONMENT

- ISO ROPS/FOPS certified
- Spring applied, hydraulic release (SAHR) brakes
- Optional monitor (cameras) to increase operator's visibility during operation
- Door interlock

## **ENVIRONMENTAL**

- Fuel efficient, clean burning Tier 2/Stage II engine
- Purifier with fume diluter

# **SERVICEABILITY**

- All daily check points easily reachable
- Quick and easy service to increase productivity

- Air, hydraulic and transmission filter change indicators
- Easy access to service points, filters and valve blocks

#### **OPERATOR'S COMFORT**

- Comfortable T-back seat
- Steering wheel ergonomically placed
- Single seat or dual seat compartment optional

#### RELIABILITY

- Proven powertrain Clark powershift transmission
- Mechanical gear control in cab
- Machine status indication lights

# **SPECIFICATIONS**

2 399mm Vehicle height Vehicle length 9 948mm Front chassis 1 800mm Vehicle width 2 752mm Rear chassis 2 752mm Ground clearance 316mm Inner turning radius 5 377mm Outer turning radius 8 477mm Gross vehicle

weight empty

Max. carrying

capacity

3 400kg

38

16 000ka

Max. passengers

## **ENGINE**

■ Type BF6L914

Power rating 92kW at 2 300rpm

Torque 430Nm at 1 500rpm

■ Fuel consumption 220g/kWh

■ Engine protection As per customer

requirements

Air cleaner Two stage

Catalytic converter

Diluter

## TRANSMISSION/TORQUE CONVERTER

 Three speed forward and reverse with integral converter

DanaT20 000 series

# **AXLES**

■ Dana 112

Rigid planetary axles

## **BRAKES**

Failsafe brake on all four wheels

 Fully enclosed, force cooled, multiple wet discs each wheel end

Service/parking/emergency type – SAHR

#### **TYRES**

■ Tyre size 35 x 15 – 15

Designed for underground mine service



## **ELECTRICAL SYSTEM**

- 24V system
- Alternator 28V/55A
- Isolation switch lockout

## **HYDRAULIC SYSTEM**

System pressure 17.5MPa

Pump type Gear

Flow rate 36 litres/min at

2 300rpm

■ Hydraulic tank capacity 170 litres

Hydraulic level switch detection

#### **FUEL SYSTEM**

Fuel tank capacity 85 litres

## **SAFETY**


- Fire extinguisher
- Reverse hooter
- Door interlock
- Marker lamps red/green
- Wheel stop blocks

## **OPTIONAL EQUIPMENT**


- Manually/automatically actuated fire suppression engine shut down
- Central lubrication management system
- Automatic lubrication system
- Halogen, LED, sealed beam lights
- Electrical gear control inside cab

## **DOCUMENTS**

- Parts manual
- Technical manual
- Risk assessment



# **SIDE VIEW**



AARD Mining Equipment is constantly striving to improve its products and therefore reserves the right to change the designs, materials, specifications and price without prior notice.

# PRODUCTS & EQUIPMENT

44 Jacobs St., Chamdor, 1739 PO Box 3992, Witbeeck 1729, South Africa

**E-mail:** info@aardme.co.za **Website:** www.aardme.com

